

Specifications

Model		DS-1LH1SCA3C-090B
Coaxial Cable		
Conductor	Material	Bare copper
	Wire Gauge	26AWG
	Diameter	0.41±0.01mm
Insulation	Material	FPE
	Diameter	2.0±0.1mm
Tape	Material	Copper foil
Braid	Material	Copper clad aluminum magnesium
	Braiding Standard	5*16*0.12mm ±0.008mm
	Braiding Density	≥80%
Jacket	Material	PVC
Impedance		75ohms
Power Cable		
Conductor	Material	Bare copper
	Quantity	3
	Diameter	11*0.16±0.008mm
Insulation	Material	SR-PVC
	Diameter	1.2±0.1mm
Jacket	Material	PVC
General		
Length		90m
Color		Black

Distributed by

Available Model

DS-1LH1SCAM592C 90m

Headquarters

No.555 Qianme Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5896
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Europe
T +31-23-5542770
saleseuro@hikvision.com

Hikvision Middle East
T +971-4-8818086
salesme@hikvision.com

Hikvision Russia
T +7-495-659-67-99
salesru@hikvision.com

Hikvision India
T +91-22-25469000
sales@pramahikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision France
T +3301-85-330-444
info.fr@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Poland
T +48-22-460-01-58
poland@hikvision.com

Hikvision UK
T +44-1629-9021-4
support.uk@hikvision.com

Hikvision Singapore
T +65-8894-4718
sg@hikvision.com

Hikvision Oceania
T +61-2-8589-4233
salesau@hikvision.com

Hikvision Hong Kong
T +852-2153-1761

Hikvision Canada
T +1-909-895-0400
sales.usa@hikvision.com